

U-shaped Floor Armrest-(Toilet Armrest)

U型落地扶手-(坐便器扶手)

Model : LR-SP

Features:

- Polished rounded corners, anti-skid and anti-falling, are not afraid of gripping with wet hands, effectively preventing accident
- Built-in thick stainless steel, double pipes are more firm and non-slip, super load-bearing 600 kg
- Anti-rust, corrosion-resistant, no deformation, safer to use
- Suitable for: toilets, stairs and other places, easy to install, easy to get
- 防滑防摔：大顆粒凸起打磨圓角防滑，有效增加阻力防止意外
- 內置加厚不鏽鋼內管，雙管加固更牢固防滑
- 不凍手、防生鏽、耐腐蝕、不變形、使用更安全
- 超強承重600斤，易安裝，輕鬆搞定
- 適用於：衛生間、樓梯等場所使用



Specifications

Product model 產品型號	LR-SP
Product function 產品功能	u-shaped floor armrest-(toilet armrest) U型落地扶手-(坐便器扶手)
Material 材質	外管尼龍+304不銹鋼內管
Installation method 安裝方式	drilling 打孔
Product bearing 產品承重	300KG
Product size 產品尺寸	60*70*5CM
Product weight 產品重量	750g
Packing Weight 包裝重量	850g
Package Size 包裝尺寸	40*9*9cm

Instructions

- ◆ 選定安裝扶手的位置，將扶手放在安裝比特上，擰開蓋子
- ◆ 選擇安裝的孔比特，建議選擇3個對稱孔比特，用鉛筆在牆面畫出安裝孔比特
- ◆ 用衝擊鑽在做標記的牆體上打孔
- ◆ 將塑膠膨脹塞放入已鑽好的孔內，膨脹塞要沒入牆內
- ◆ 將扶手放在孔比特處，扶手底板上的孔和牆面的孔對準，將螺絲穿過底板用螺絲刀固定
- ◆ 確認6顆螺絲是否都固定牢固
- ◆ 確認OK後，將底板面蓋蓋好，固定在卡位處

◆ 注意事項：

1. 安裝前請確認安裝牆面是否牢固(可安裝牆：混凝土、輕質混凝土、實心磚、天然緻密石材、加固牆體可承重牆體)
2. 需加固才可安裝牆體：多孔磚、灰砂磚、薄空心磚、單木板牆等中等低承受力牆體
(注：石膏牆無法安裝，如空心牆厚度較薄，請自行購買中等空壁虎螺絲安裝)
3. 實體牆轉孔：若發現牆質疏鬆承載力不強，或者安裝螺絲是輕鬆好擰，請再次確認牆體受力度
4. 如有問題，請換個位置安裝或加固處理，可往牆體裡灌注水泥等其凝固後再轉孔安裝
5. 高度注意：離地類產品安裝高度，以使用人員自身用途為準